

TEMADUR ACCELERATOR

DESCRIPTION

An accelerator solution which makes the curing faster.

PRODUCT FEATURES AND RECOMMENDED USES

- Used to accelerate the curing of TEMADUR 20, 50 and 90 polyurethane paints and TEMADUR CLEAR varnish.
- Facilitates early tapeing of painted surfaces.
- ♦ Not suitable for TEMADUR HB polyurethane paints.

TECHNICAL DATA

Specific gravity 0.9 kg / l

Product code 990 0746

Recommended usage Max. 10 vol.-% of the amount of the paint/hardener mixture.

Influence on drying times

Amount of accelerator, + 23 °C	0 %	5 %	10 %
Pot life	4 h	1 h	½ h
Tapeable	24 h	8 h	4 h

Application

Mix base and hardener. Add the required amount of accelerator. Thin with Thinner 1048, if necessary, and mix thoroughly. <u>Pay attention to the shortened pot life</u> and start the painting work without delay.

HEALTH AND SAFETY

Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets.

A health and safety data sheet is available on request from Tikkurila Coatings Oy.

For professional use only.

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. When necessary verify the validity of the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of the standards ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

mko310306/tmk020106/990 0746