

TEMADUR STRUCTURE EXTRA

DESCRIPTION

An additive for polyurethane paints.

PRODUCT FEATURES AND RECOMMENDED USES

- Is used in TEMADUR polyurethane paints and varnishes in order to roughen the finish.
- Causes a rough finish and reduces the gloss of the paint film.
- Improves the abrasion resistance of the paint film.

TECHNICAL DATA

Specific gravity 0.94 kg / I

Product code and recommended amount to be added

990 1071

2 - 8 volume-% of the amount of paint/hardener mixture.

Directions for use

Mix TEMADUR base and hardener. Add a wanted amount of TEMADUR STRUCTURE EXTRA and thin with Thinner 1048. Stir thoroughly. Check if the finish is as wanted by painting a small test area. If the surface is too rough, add TEMADUR paint mixture or if the surface is too smooth add TEMADUR STRUCTURE EXTRA.

VOC

The Volatile Organic Compounds amount to 550 ± 20 g/l of solution.

HEALTH AND SAFETY

Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets.

A health and safety data sheet is available on request from Tikkurila Coatings Oy.

For professional use only.

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. When necessary verify the validity of the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of the standards ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

tmk020802/990 1071